








**51.2V**

# LiFePO4 Battery Pack

**Low-voltage**

**10.5kWh**

## Features

-  Built-in fire protection system.
-  Scalable expansion up to 15 pcs in parallel.
-  Built-in WiFi for remote monitor the battery pack data.
-  LiFePO4: Higher safe performance and longer cycle life.
-  Multiple Protection with built-in smart BMS, breaker and fuse.
-  Compatible with leading inverter brands.
-  Up to 7-year long warranty.



**FLA48200-P**



Model	FLA48200-P
Battery Type	LiFePO4
Nominal Energy	10.5kWh
Nominal Voltage	51.2V
Operating Voltage	44.8-57.6V
Recommend Charge/Discharge Current[1]	≤150A
Recommend Charge/Discharge Power[1]	≤7,500W
Maximum Charge/Discharge Current(15s)	200A
Maximum Charge/Discharge Power(15s)	10,000W
Scalability	Max. 15 pcs in Parallel(157.4kWh)
Depth of Discharge(DOD)	≥95%
Communication	RS485/CAN
Protection Degree	IP21
Cycle Life	≥ 6,000 Cycles (25°C±2°C,0.5C/0.5C,90%DOD,70%EOL)
Charging Temperature Range	0°C~+55 °C
Discharging Temperature Range	-20°C~+55 °C
Display Type	LCD+LED
Installation	Wall-Mounted / Floor-Mounted
Protection	Built-in smart BMS, Breaker, Fuse
Warranty Period	7 Years
Certification	UN38.3、CE-EMC、 IEC 62619
Product Weight	92KG
Package Weight	115.6KG
Product Dimension	783X450X274MM
Package Dimension	900X570X450MM

[1] Max. Continuous Charge/Discharge Current is Affected by Temperature and SOC.

\*Product specifications may vary during continuous improvements. Please contact us for latest details.

\*Refer to Felicitysolar's Warranty Policy for applicable conditions.

## Product Display



Built-in WiFi/Bluetooth for Remote Monitoring



Aerosol Fire Extinguishing System



Supports wall-mounted Installation



Wide Inverter Compatibility

